## (19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 17 February 2005 (17.02.2005)

PCT

## (10) International Publication Number WO 2005/014281 A1

(51) International Patent Classification7:

B32B 27/04

(21) International Application Number:

PCT/US2004/021053

(22) International Filing Date: 29 June 2004 (29.06.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

10/627,847

25 July 2003 (25.07.2003) US

(71) Applicant: BUILDING MATERIALS INVESTMENT CORPORATION [US/US]; 300 Delaware Avenue, Suite 303, Wilmington, DE 19801 (US).

(72) Inventor: YANG, Li-Ying; 34 Windemere Ct., Whippany, NJ 07981 (US).

(74) Agents: MAUE, Marilyn, J. et al.; Legal Department, Bld. 8, Gaf Materials Corporation, 1361 Alps Road, Wayne, NJ 07470 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



(54) Title: SINGLE PLY THERMOPLASTIC POLYOLEFIN (TPO) ROOFING MEMBRANES HAVING SUPERIOR HEAT SEAM PEEL STRENGTHS AND LOW TEMPERATURE FLEXIBILITY